

 TUBE AND PIPE

**North American Headquarters**  
**Quaker Chemical Corporation**  
One Quaker Park  
901 E. Hector Street  
Conshohocken, PA 19428-2380  
U.S.A.  
+1.610.832.4000

**European Headquarters**  
**Quaker Chemical B.V.**  
Industrieweg 7  
1422 AH Uithoorn  
The Netherlands  
+31.297.544644

**Asia/Pacific Headquarters**  
**Quaker Chemical (China) Co., Ltd.**  
No. 619 TianYing Road  
Qingpu Industrial Park  
Shanghai 201700  
People's Republic of China  
+86.21.3920.1666

**South American Headquarters**  
**Quaker Chemical Indústria e Comércio Ltda.**  
Avenida Brasil, no 44.178  
Distrito Industrial de Campo Grande  
23.078-000 - Rio de Janeiro - RJ  
Brazil  
+55.21.3305.1800

[quakerchem.com](http://quakerchem.com)



Tube and Pipe  
Product Line



# Tube and Pipe Product Line



| PRODUCT                      | CATEGORY                  | USE CONCENTRATION | METALS   |             |            |           |              | APPLICATION   |
|------------------------------|---------------------------|-------------------|--|-------------|------------|-----------|--------------|---|
|                              |                           |                   | Hot rolled   | Cold rolled | Galvanized | Stainless | Super Duplex |   |
| <b>METAL FORMING FLUIDS</b>  |                           |                   |  |             |            |           |              |   |
| QUAKERCOOL® 2854             | Synthetic                 | 4 - 10%           |  |             | ●          |           |              | Tube forming  |
| QUAKERCOOL® 2871             | True Solution Synthetic   | 4 - 10%           | ●  | ●           |            |           |              | Tube forming  |
| QUAKERCOOL® 2856             | Synthetic                 | 3 - 5%            | ●  | ●           |            |           |              | Tube forming, hydrotesting                                    |
| ATLAS™ 3374 - 140            | Heavy EP Oil              | 100%              |  |             |            | ●         |              | Pilgering OD  |
| ATLAS™ 3374 - DPX            | Heavy EP Paste            | 100%              |  |             |            | ●         | ●            | Pilgering OD and ID   |
| <b>METAL REMOVAL FLUIDS</b>  |                           |                   |  |             |            |           |              |   |
| QUAKERCOOL® 750 TP           | Synthetic Emulsion        | 3 - 12%           | ●  | ●           |            |           |              | Heavy duty machining and grinding, threading and hydrotesting |
| QUAKERCOOL® 2776             | True Solution Synthetic   | 5 - 10%           | ●  | ●           |            |           |              | Heavy duty machining and grinding, threading                  |
| QUAKERCUT® 012E              | Full Synthetic            | 100%              | ●  | ●           | ●          |           |              | Heavy duty machining and grinding, cutting, sawing            |
| <b>CLEANERS</b>              |                           |                   |  |             |            |           |              |   |
| QUAKERCLEAN® LFE             | Alkaline                  | 5 - 20%           | ●  | ●           | ●          | ●         |              | Cleaning  |
| <b>CORROSION PREVENTIVES</b> |                           |                   |  |             |            |           |              |   |
| FERROCOTE® 364 BFT1          | Oil/Solvent               | 100%              | ●  | ●           |            |           |              | Medium-duty corrosion protection (6-12 months)                |
| FERROCOTE® 5856 BFT1         | Oil/Solvent               | 100%              | ●  | ●           |            |           |              | Medium-duty corrosion protection (6-12 months)                |
| <b>METAL PROTECTING</b>      |                           | VOC (LBS/GALLON)  |  |             |            |           |              |   |
| QUAKERCOAT® 104              | Water based               | 0                 | ●  | ●           | ●          |           |              | Acrylic permanent coating                                     |
| QUAKERCOAT® 172              | Water based               | 2                 | ●  | ●           | ●          |           |              | Acrylic permanent coating                                     |
| QUAKERCOAT® 200T             | Water based               | 1.5               | ●  | ●           | ●          |           |              | Acrylic permanent coating                                     |
| QUAKERCOAT® 552              | Solvent based             | 3.5               | ●  | ●           | ●          |           |              | Alkyd permanent coating                                       |
| QUAKERCOAT® 021              | UV                        | 0                 | ●  | ●           | ●          |           |              | Epoxy acrylate permanent coating                              |
| QUAKERCOAT® 036              | UV                        | 0                 | ●  | ●           | ●          |           |              | Epoxy acrylate permanent coating                              |
| <b>HYDRAULIC FLUIDS</b>      |                           |                   | <b>BENEFITS</b>  |             |            |           |              |   |
| QUINTOLUBRIC® 888            | HFD-U: Polyol Ester based | As delivered      | Excellent lubrication, excellent shear stability, fire resistant, simple waste treatment     |             |            |           |              | Casting   |
| QUINTOLUBRIC® 702-46 RD      | HFC: Water Glycol         | As delivered      | Maximum fire resistance, enhanced job site safety, reduced downtime, lower maintenance costs |             |            |           |              | Casting   |